### ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES UP TO 500 Kg AND 1100 Kg, 24 Vdc



#### **PLUS**

SUN has extremely silent mechanics, thanks to a neat design and the use of high performance materials

High technological materials resistant to all weather conditions

UV-resistant plastic covers, FASTLINE drak grey cover for SUN5024F

Extremely silent mechanics, protected by robust die-casted and powder-coated aluminum body

The release system is ergonomic, efficient and easily accessible

Integrated back-up battery (optional)

Gear reduction with extra-large bearing with high performance

FASTLE

Magnetic limit switch for SUN5024F, for others upon request

Opening speed up to 40 cm/s for SUN5024F

Version with external 24V transformer available (SPLIT24V)

With 24 Vdc control unit 14A (page 72 for technical details)



Control board 14A



Robust gear reduction with self-standing bearing



**Built-in LED light** 



DYL handheld programmer with display for easy programming

### MODELS

(	CODE	DESCRIPTION	
چې 🛞	SUN5024F	For sliding gates up to 500 Kg, FAST, 24 Vdc motor, control unit with slowdown and magnetic limit switch, with 14AF control board. FASTLINE dark grey cover.	Ð
چې 🚳	SUN11024	For sliding gates up to 1100 Kg, 24 Vdc motor, control unit with slowdown and electric limit switch, with 14A control board	
چې 🛞	SUN5024FS	For sliding gates up to 500 Kg, FAST, 24 Vdc motor, control unit with slowdown and magnetic limit switch, with 14AF control board. FASTLINE dark grey cover. <b>External transformer SPLIT24V</b>	Ð
جي 🚱	SUN11024S	For sliding gates up to 1100 Kg, 24 Vdc motor, control unit with slowdown and electric limit switch, with 14A control board. External transformer SPLIT24V	

		SUN5024F	SUN11024
MECHANICAL DATA			
speed	cm/s	40* 푿	20*
torque	Nm	23	38
working cycle	%	80	80
ELECTRICAL DATA			
control board		14AF	14A
power	Vac	230	230
consumption	А	1,3	1,3
absorbed power	W	300	300
capacitor	μF	-	-
thermoprotection	°C	-	-
integrated lights		yes	yes
GENERIC DATA			
protection degree	IP	44	44
dimensions (L - D - H)	mm	330 - 210 - 300	330 - 210 - 300
weight	kg	13	13
working temperature	°C	-20 + 55	-20 + 55
gate maximum weight	Kg	500	1100

\* variable according to the gate weight

## **SUN KIT**

	CODE	DESCRIPTION	
2950	KSUN5024F	Kit for sliding gates up to 500 kg, FAST, 24 Vdc motor, control unit with slowdown, magnetic limit switch. With night light function included (control unit 14AF)	
2999	KSUN11024	Kit for sliding gates up to 1100 kg, 24 Vdc motor, control unit with slowdown, electric limit switch. With night light function included (control unit 14A)	
2939	KSUN5024FS	Kit for sliding gates up to 500 kg, FAST, 24 Vdc motor, control unit with slowdown, magnetic limit switch. With night light function included (control unit 14AF). External transformer SPLIT24V	
<b>(4</b> )	KSUN11024S	Kit for sliding gates up to 1100 kg, 24 Vdc motor, control unit with slowdown, electric limit switch. With night light function included (control unit 14A). <b>External transformer SPLIT24V</b>	

# **KIT COMPONENTS**



	• •			And the second second		
	RX4X (1 pc)	SUB-44R (1 pc) + SUB-44WR (1 pc)	CPSC-50 (1 pc)	RACK6 (4 pcs)	TS (1 pc)	
KSUN5024F	٠	٠	٠	٠	٠	
KSUN11024	٠	٠	٠	٠	٠	
KSUN5024FS	٠	•	٠	٠	•	
KSUN11024S	٠	٠	٠	٠	٠	

FASTLINE